

**KOBELCO**

SK330-10/SK350LC-10

**SK330 SK350<sub>LC</sub>**



**We Save You Fuel**  
Achieving a Low-Carbon Society

# Power Meets Efficiency



**SK330 SK350 LC**



20%  
Higher fuel efficiency  
means  
"Efficiency"

Increase in  
productivity  
means  
"Power"

Compared to S-mode on the SK330/350LC-8

To urban centers, and to mines around the world. Kobelco's all-out innovation brings you durable earth-friendly construction machinery that's equal to any task, at sites all over the planet. Increased power and even greater fuel economy bring higher efficiency to any project. Kobelco SK330/350LC machines are also more durable than ever, able to withstand the rigors of the toughest job sites. It all adds up to new levels of value that are a step ahead of the times. Also, this machine conforms to Stage V Exhaust Emission Standards, thanks to its significantly reduced NOx\* emissions. While focusing on the global environment of the future, Kobelco offers next-generation productivity to meet the need for lower life cycle costs and exceed the expectations of customers the world over.

\* NOx: Nitrogen Oxide



# Evolution Continues, with Improved Fuel Efficiency.


KOBELCO  
LC69E  
D1049P1

KOBELCO  
LC69E  
D1049P1

## Hydraulic System: Revolutionary Technology Saves Fuel

### Arm Interflow System NEW


When lowering the boom, this system uses the downward force generated by the boom's weight to push fluid to the shovel arm. This greatly reduces the need to apply power from outside the system.



### Hydraulic circuit reduces energy loss

We have made every effort to enhance fuel efficiency by minimizing hydraulic pressure resistance, improving the hydraulic line layout to control friction resistance loss and minimizing valve resistance.

Improved hydraulic piping is an effective means of reducing pressure loss.



## In Pursuit of Improved Fuel Efficiency

### Operation Mode

Fuel consumption is lower in ECO-mode/S-mode in comparison with the previous model (Generation 8).

■ Compared to previous models


- E** ECO-mode  
... About **32%** improvement  
(compared to S-mode on the SK350LC-8)
- S** S-mode  
... About **20%** improvement
- H** H-mode  
... About **7%** improvement

**Always and Forever. Yesterday, Today, and Tomorrow. We're Obsessed with Fuel Efficiency.**

Over the past 10 years, KOBELCO has achieved an average fuel consumption reduction of 47% across its fleet. We vow to lead the industry in improving fuel efficiency.

■ Compared to SK350LC-6 model (2006)

**E** ECO-mode (SK350LC-10)  
... About **47%** improvement



### AIS (Auto Idle Stop)

If the boarding/disembarking lever is left up, the engine will stop automatically. This eliminates wasteful idling during standby, saving fuel and reducing CO<sub>2</sub> emissions as well.

**20%**  
Higher fuel efficiency  
means  
"Efficiency"



The new arm interflow system more efficiently controls hydraulic fluid flow, and significant reduction of in-line resistance and pressure loss boosts fuel efficiency by about 20%\*1. The engine, already well-known for its environmental performance has a new SCR\*2 system, and its reduced NOx emissions means the engine now meets Stage V Standards.

\*1. Compared to S-mode on the SK330/350LC-8  
\*2. SCR: Selective Catalytic Reduction

**Engine Meets Stage V Standards**

**Reduces Fuel Consumption and Minimizes Exhaust Emissions**


Hino engines are renowned for fuel efficiency and environmental performance, and Kobelco has tuned these powerplants especially for construction machinery. The pressure within the common rail fuel injection system, the VG turbo, and the exhaust gas after-treatment system reduce exhaust PM\*3 while the large-capacity EGR cooler sharply reduces the formation of NOx gases.



\*3 PM: Particulate Matter

**VG Turbo Reduces PM**

The variable-geometry turbocharger adjusts air intake to maximize combustion efficiency. At low engine speeds the nozzles are closed, the turbo speed increased and air intake is boosted. This helps lower fuel consumption.




**SCR System with Urea** NEW

The engine exhaust system has an SCR system that converts NOx emissions into harmless nitrogen and water. Combining this with a post-exhaust gas treatment system that captures and disposes of PM, the SK330/SK350LC has a much cleaner exhaust that meets Stage V exhaust emission standards.


■ NOx reduction rate  
(Compared to previous models)

About **80%** decrease



**EGR Cooler Reduces NOx**

Cooled exhaust gases from the EGR cooler are mixed with fresh air in the intake. The recirculated air lowers the combustion temperature which reduces NOx.



# More Power and Higher Efficiency.

The highly efficient hydraulic system minimizes fuel consumption while maximizing power. With nimble movement and ample digging power, this excavator promises to improve your job productivity.

Improved fuel efficiency contributes to high performance

## Superior Digging Volume

This excavator offers dynamic digging force even as it minimizes fuel consumption rates, achieving class-leading work volume.

■ Digging volume/hour  
(Compared to H-mode on previous models)



■ Max. Bucket Digging Force

Normal: **222kN**  
With power boost: **244kN**


■ Max. Arm Crowding Force

Normal: **163kN**  
With power boost: **180kN**

\*Values are for HD arm (3.30m)




## Get More Done Faster with Superior Operability



\*Values are for HD arm (3.30m)

### Piping for Quick Hitch



A quick hitch hydraulic line, which speeds up attachment changes, is fitted as standard.

### A Light Touch on the Lever Means Smoother, Less Tiring Work **NEW**



It takes 38% less effort to work the operation lever, which reduces fatigue over long working hours or continued operations (Compared to SK330LC-8).

### Top Class Traveling Force

Powerful traveling force and pulling force deliver plenty of speed when climbing slopes or negotiating bad roads, and the agility to change direction swiftly and smoothly.





■ Drawbar Pulling Force: **332kN**

## Operator-friendly Features Include Controls that Are Easy to See, Easy to Use

### Multi-Display in Color

Brilliant colors and graphic displays are easy to recognize on the LCD multi-display in the console. The display shows fuel consumption, maintenance intervals, and more.

- 1 Analog gauge provides an intuitive reading of fuel level and engine water temperature
- 2 Green indicator light shows low fuel consumption during operation
- 3 PM accumulation display (left)/Urea level gauge (right)
- 4 Fuel consumption/Switch indicator for rear camera images
- 5 Digging mode switch
- 6 Monitor display switch




PM accumulation/display Urea level gauge




Fuel consumption

MAINTENANCE		6.7h
	INTERVAL	REMAINING TIME
ENGINE OIL	500	495
FUEL FILTER	500	495
HYD. FILTER	1000	995
HYD. OIL	5000	4995

Maintenance



Breaker mode



Nibbler mode




Rearview monitoring

### One-Touch Attachment Mode Switch

A simple flick of a switch converts the hydraulic circuit and flow amount to match attachment changes. Icons help the operator to confirm the proper configuration at a glance.

# Increased Power, with Enhanced Durability to Maintain the Machine's Value




## Built to Operate in Tough Working Environments

The attachment has been reinforced to handle a higher work volume, with greater power and excellent durability that can withstand demanding work conditions.


### 1 Enlarged Reinforcement of the Arm Foot

HD: Base plate thickness has been increased 1.3 times.



### 2 Modified Foot Boss Shape

The arm foot boss shape has been modified and improved to distribute stress, delivering 2.6 times more strength for tasks like digging next to a wall.





Increase in  
productivity  
means  
"Power"

Structural design increases strength,  
while eliminating hydraulic problems.  
Enhanced durability takes  
productivity to a new level.



## Improved Filtration System Reliability

Clean, contaminant-free fuel and hydraulic fluid are essential to stable performance. The improved filtration systems reduce the risk of mechanical trouble and enhance longevity and durability.


### Hydraulic Fluid Filter **NEW**

Recognized as the best in the industry, our premium fine filter separates out even the smallest particles. New cover prevents contamination when changing filters.



### Hydraulic Fluid Filter Clog Detector **NEW**

Pressure sensors at the inlet and outlet of the hydraulic fluid filter monitor differences in pressure to determine the degree of clogging. If the difference in pressure exceeds a predetermined level, a warning appears on the multi-display, so any contamination can be removed from the filter before it reaches the hydraulic fluid reservoir.




### Double-Element Air Cleaner

The large-capacity element features a double-filter structure that keeps the engine running clean even in industrial environments.



### Fuel Filter **NEW**

The pre-filter, with built-in water separator maximizes filtering performance.



# Comfortable Cab Is Now Safer than Ever.

A work environment that is quieter and more comfortable. A cab that puts the operator first is key to improved safety.



The picture is optional air suspension seat.

## Comfort

### Super-Airtight Cab



The high level of air-tightness keeps dust out of the cab.


### Quiet Inside

The high level of air-tightness ensures a quiet, comfortable cabin interior.

### Low Vibration

Coil springs absorb small vibrations, and high suspension mounts filled with silicone oil reduce heavy vibration. The long stroke achieved by this system provides excellent protection from vibration.

Twice the stroke of a conventional mount



### Broad View Liberates the Operator

The front window features one large piece of glass without a center pillar on the right side for a wide, unobstructed view.

## Air Conditioner Register behind the Seat

**NEW**



The large air-conditioner has registers on the back pillars that blow from behind and to the right and left of the operator's seat. They can be adjusted to put a direct flow of cool/warm air on the operator, which means a more comfortable operating environment.

## More Comfortable Seat Means Higher Productivity



Seat suspension absorbs vibration



Seat recliner can be pushed back flat



Double slides allow adjustment for optimum comfort



## Large Cab Is Easy to Get in and out of

The expanded cab provides plenty of room for a large door, more headroom and smoother entry and exit.


## Interior Equipment Adds to Comfort and Convenience



Automatic AM/FM radio



USB pin/12V power outlet



Spacious storage tray



Large cup holder

## Safety

### ROPS Cab

ROPS (Roll-Over-Protective Structure)-compliant cab clears ISO standards (ISO-12117-2: 2008) and ensures greater safety for the operator should the machine tip over.




TOP Guard is fitted as standard.

## Expanded Field of View for Greater Safety




Rear View Camera

Right side View Camera



Rear view



Hammer for emergency exit

### Right Side Camera Available as an Option

The standard rear-view camera and optional right side camera help the operator maintain an enhanced margin of safety all around the machine.

Rear view shows the area directly behind the cab.

# GEOSCAN

## Excavator Remote Monitoring System




### Remote Monitoring for Peace of Mind

GEOSCAN uses satellite communication and internet to relay data, and therefore can be deployed in areas where other forms of communication are difficult. When a hydraulic excavator is fitted with this system, data on the machine's operation, such as operating hours, location, fuel consumption, and maintenance status can be obtained remotely.


### Direct Access to Operational Status

#### Location Data

• Accurate location data can be obtained even from sites where communications are difficult.



Latest location




Location records

Type of Operation	Working Hrs	Ratio
Total Working Hrs	169 Hrs	100 %
Digging Hrs	72.2 Hrs	43 %
Traveling Hrs	18.3 Hrs	11 %
Idle Hrs	15.9 Hrs	9 %
Opt Att Hrs	62.5 Hrs	37 %
Crane Mode Hrs	0 Hrs	0 %

Work data

## Operating Hours

- A comparison of operating times of machines at multiple locations shows which locations are busier and more profitable.
- Operating hours on site can be accurately recorded, for running time calculations needed for rental machines, etc.



Daily report

## Fuel Consumption Data

- Data on fuel consumption and idling times can be used to indicate improvements in fuel consumption.

Work mode	Working Hrs	Total Fuel Consumption
H mode	2:06	24.5 L
S mode	0:00	0.0 L
E mode	169:19	1489.7 L
<b>TOTAL</b>	<b>171:25</b>	<b>1514.2 L</b>

Fuel consumption

## Graph of Work Content

- The graph shows how working hours are divided among different operating categories, including digging, idling, traveling and optional operations.



Work status

## Maintenance Data and Warning Alerts

### Machine Maintenance Data

- Provides maintenance status of separate machines operating at multiple sites.
- Maintenance data is also relayed to KOBELCO service personnel, for more efficient planning of periodic servicing.

Model	Serial No.	Hour Meter	Engine Oil
SK135SRLC-3/SK140SRL	<a href="#">YH07-09721</a>	734 Hr	434
SK135SRLC-3/SK140SRL	<a href="#">YH07-09789</a>	73 Hr	429
SK210LC-9	<a href="#">YQ13-10454</a>	960 Hr	58
SK210LC-9	<a href="#">YQ13-10481</a>	549 Hr	498
SK75SR-	<a href="#">YT08-30374</a>		

Maintenance

### Warning Alerts

- This system warns an alert if an anomaly is sensed, preventing damage that could result in machine downtime.

### Alarm Information Can Be Received through E-mail

- Alarm information or maintenance notice can be received through E-mail, using a computer or cell phone.



Alarm messages can be received on mobile device.

### Daily/Monthly Reports

- Operational data downloaded onto a computer helps in formulating daily and monthly reports.

## Security System

### Engine Start Alarm

- The system can be set an alarm if the machine is operated outside designated time.

Engine start alarm outside prescribed work time

### Area Alarm

- It can be set an alarm if the machine is moved out of its designated area to another location.

Alarm for outside of reset area




## Easy, On-the-Spot Maintenance NEW

There is ample space in the engine compartment for a mechanic to do maintenance work inside. The distance between steps is lower so entry and exit is easier. And the mechanic can work in comfort, without contortions or unnatural body positions. Finally, the hood is lighter and easier to raise and lower.



Generous space for maintenance work



Step/Hand rail



Urea tank



Double-element air cleaner


Positioned where the step opens

## Maintenance Work, Daily Checks, Etc. Can Be Done from Ground Level

The layout allows for easy access from the ground for many daily checks and regular maintenance tasks.



Fuel filter/Pre-filter



Right side



Engine oil filter



Left side

- ① Fuel filter
- ② Pre-filter
- ③ Engine oil filter

Laid out for easy access to radiator and cooling system elements

# Efficient Maintenance Keeps the Machine in Peak Operating Condition.




MAINTENANCE			
		⌚ 6.7h	
	INTERVAL	REMAINING TIME	EXCHANGE DAY
ENGINE OIL	500 Hr	495 Hr	--/--/--
FUEL FILTER	500 Hr	495 Hr	--/--/--
HYD. FILTER	1000 Hr	995 Hr	--/--/--
HYD. OIL	5000 Hr	4995 Hr	--/--/--

## Machine Information Display Function

Examples of displaying maintenance information

- Displays only the maintenance information that's needed, when it's needed
- Self-diagnostic function provides early-warning detection and display of electrical system malfunctions
- Service-diagnostic function makes it easier to check the status of the machine
- Record function of previous breakdowns including irregular and transient malfunction

## More Efficient Maintenance Inside the Cab



Easy-access fuse box

More finely differentiated fuses make it easier to locate malfunctions.



Air conditioner filters

Internal and external air conditioner filters can be easily removed without tools for cleaning.



DPF reactivation switch

If the monitor warning goes off, the filter should be reactivated manually using a switch.

## Easy Cleaning




Crawler frame

Special crawler frame design is easily cleaned of mud.



Detachable two-piece floor mat

Detachable two-piece floor mat with handles for easy removal. A floor drain is located under floor mat.



Engine oil pan

Engine oil pan equipped with drain valve.

Long-life hydraulic oil:  
**5,000**  
hours

## Long-Interval Maintenance

Long-life hydraulic oil reduces cost and labor.

Replacement cycle:  
**1,000**  
hours

## Highly Durable Premium Fine Filter

The high-capacity hydraulic oil filter incorporates glass fiber with superior cleaning power and durability.





## Engine

Model	HINO JO8EVV-KSDK
Type	Direct injection, water-cooled, 4-cycle diesel engine with turbocharger, intercooler, Stage V certified
No. of cylinders	6
Bore and stroke	112 mm x 130 mm
Displacement	7.684 L
Rated power output	201 kW/2,100 min <sup>-1</sup> (ISO 9249)
	213 kW/2,100 min <sup>-1</sup> (ISO 14396)
Max. torque	988 N·m/1,600 min <sup>-1</sup> (ISO 9249)
	1,017 N·m/1,600 min <sup>-1</sup> (ISO 14396)



## Hydraulic System

Pump	
Type	Two variable displacement pumps + One gear pump
Max. discharge flow	2 x 294 L/min, 1 x 21 L/min
	Extra gear pump 1 x 43 L/min
Relief valve setting	
Boom, arm and bucket	34.3 MPa {350 kgf/cm <sup>2</sup> }
Power Boost	37.8 MPa {385 kgf/cm <sup>2</sup> }
Travel circuit	34.3 MPa {350 kgf/cm <sup>2</sup> }
Swing circuit	29.0 MPa {296 kgf/cm <sup>2</sup> }
Control circuit	5.0 MPa {50 kgf/cm <sup>2</sup> }
Pilot control pump	Gear type
Main control valve	8-spool
Oil cooler	Air cooled type



## Swing System

Swing motor	Axial piston motor
Brake	Hydraulic; locking automatically when the swing control lever is in neutral position
Parking brake	Oil disc brake, hydraulic operated automatically
Swing speed	10.0 min <sup>-1</sup> {rpm}
Swing torque	119.6 kN·m
Tail swing radius	3,600 mm
Min. front swing radius	4,310 mm



## Attachments

Backhoe bucket and combination

Use	Backhoe bucket			
			Normal digging	
Bucket capacity	Heaped (ISO7451)	m <sup>3</sup>	1.20	1.60
	Struck (ISO7451)	m <sup>3</sup>	0.84	1.20
Opening width	With side cutter	mm	1,240	1,570
	Without side cutter	mm	1,110	1,450
No. of teeth			4	5
Bucket weight		kg	930	1,080
Combination	2.60 m short arm		○	◎
	3.30 m standard arm		○	△
	4.15 m long arm		○	△

◎ Standard ○ Recommend △ Loading only × Not recommended



## Travel System

Travel motors	2 x axial-piston, two-step motors
Travel brakes	Hydraulic brake per motor
Parking brakes	Oil disc brake per motor
Travel shoes	45 (48) each side
Travel speed	5.6/3.3 km/h
Drawbar pulling force	332 kN {ISO 7464}
Gradeability	70 % {35°}

( ) shows SK350LC



## Cab & Control

Cab	
All-weather, sound-suppressed steel cab mounted on the high suspension mounts filled with silicone oil and equipped with a heavy, insulated floor mat.	
Control	
Two hand levers and two foot pedals for travel	
Two hand levers for excavating and swing	
Electric rotary-type engine throttle	



## Boom, Arm & Bucket

Boom cylinders	140 mm x 1,550 mm
Arm cylinder	170 mm x 1,788 mm
Bucket cylinder	150 mm x 1,193 mm



## Refilling Capacities & Lubrications

Fuel tank	503 L
Cooling system	35 L
Engine oil	28.5 L
Travel reduction gear	2 x 8.0 L
Swing reduction gear	7.4 L
Hydraulic oil tank	245 L tank oil level
	410 L hydraulic system
DEF/Urea tank	83 L



## Working Ranges

Unit: m


Range	Arm	6.5 m Boom		
		Short 2.6 m	Standard 3.3 m	Long 4.15 m
a-Max. digging reach		10.61	11.26	11.97
b-Max. digging reach at ground level		10.4	11.06	11.79
c-Max. digging depth		6.86	7.56	8.41
d-Max. digging height		10.26	10.58	10.7
e-Max. dumping clearance		7.06	7.37	7.53
f-Min. dumping clearance		3.32	2.62	1.77
g-Max. vertical wall digging depth		5.84	6.61	7.15
h-Min. swing radius		4.46	4.31	4.43
i-Horizontal digging stroke at ground level		4.21	5.82	7.21
j-Digging depth for 2.4 m (8') flat bottom		6.67	7.4	8.27
Bucket capacity ISO heaped m <sup>3</sup>		1.6	1.4	1.2

## Digging Force (ISO 6015)

Unit: kN

Arm length	Short 2.6 m	Standard 3.3 m	Long 4.15 m
Bucket digging force	222 244*	222 244*	222 244*
Arm crowding force	205 225*	163 180*	140 154*

\*Power Boost engaged.




## Dimensions

Arm length	Short 2.6 m	Standard 3.3 m	Long 4.15 m
A Overall length	11,380	11,300	11,330
B Overall height (to top of boom)	3,690	3,420	3,590
C Overall width of crawler	3,190		
D Overall height (to top of cab)	3,200		
E Ground clearance of rear end*	1,190		
F Ground clearance*	500		
G Tail swing radius	3,600		

Unit: mm

G' Distance from center of swing to rear end	3,600
H Tumbler distance	3,720 (4,050)
I Overall length of crawler	4,630 (4,960)
J Track gauge	2,590
K Shoe width	600
L Overall width of upperstructure	3,120

\*Without including height of shoe ( ) shows 350LC






## Operating Weight & Ground Pressure

In standard trim, with standard boom, 3.3 m arm, and 1.4 m<sup>3</sup> ISO heaped bucket

Shaped	Triple grouser shoes (even height)				
		mm	600	700	800
Overall width of crawler	SK330	mm	3,190	3,290	3,390
	SK350LC	mm	3,190	3,290	3,390
Ground pressure	SK330	kPa (kgf/cm <sup>2</sup> )	73	64	57
	SK350LC	kPa (kgf/cm <sup>2</sup> )	69	60	53
Operating weight	SK330	kg	36,100	36,800	37,200
	SK350LC	kg	36,700	37,600	38,000

# Lifting Capacities



A: Reach from swing centerline to arm top  
 B: Arm top height above/below ground  
 C: Lifting capacities in Kilograms  
 Bucket: Without bucket  
 Relief valve setting: 37.8 MPa (385 kgf/cm<sup>2</sup>)

SK330		Boom: 6.5 m Arm: 3.3 m, Bucket: without Shoe: 600 mm (Heavy Lift)															
A \ B		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m		9.0 m		At Max. Reach		Radius	
9.0 m	kg														*6,370	*6,370	6.56 m
7.5 m	kg									*7,800	*7,800				*5,840	*5,840	7.86 m
6.0 m	kg									*7,920	*7,920				*5,650	*5,650	8.71 m
4.5 m	kg							*9,710	*9,710	*8,480	7,650	*7,840	5,710	*5,650	5,440	9.25 m	
3.0 m	kg					*15,070	*15,070	*11,140	10,090	*9,220	7,310	7,720	5,550	*5,840	5,070	9.52 m	
1.5 m	kg					*17,270	14,140	*12,400	9,500	9,840	6,980	7,540	5,390	*6,210	4,940	9.54 m	
G.L.	kg					*18,030	13,650	*13,140	9,120	9,590	6,750	7,420	5,270	*6,840	5,020	9.33 m	
-1.5 m	kg			*15,400	*15,400	*17,660	13,550	13,090	8,960	9,470	6,640			7,560	5,360	8.85 m	
-3.0 m	kg	*17,520	*17,520	*22,230	*22,230	*16,350	13,680	*12,470	9,000	9,520	6,690			*8,620	6,110	8.07 m	
-4.5 m	kg			*18,150	*18,150	*13,770	*13,770	*10,460	9,260					*8,520	7,750	6.88 m	

SK330		Boom: 6.5 m Arm: 4.15 m, Bucket: without Shoe: 600 mm (Heavy Lift)														
A \ B		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m		9.0 m		At Max. Reach		Radius
9.0 m	kg									*5,080	*5,080			*4,780	*4,780	7.56 m
7.5 m	kg													*4,470	*4,470	8.71 m
6.0 m	kg									*6,880	*6,880	*6,590	5,860	*4,360	*4,360	9.49 m
4.5 m	kg									*7,510	*7,510	*6,980	5,710	*4,380	*4,380	9.98 m
3.0 m	kg			*21,130	*21,130	*13,030	*13,030	*9,930	*9,930	*8,340	7,310	*7,410	5,500	*4,530	4,430	10.23 m
1.5 m	kg					*15,740	14,360	*11,400	9,530	*9,180	6,920	7,440	5,280	*4,820	4,300	10.25 m
G.L.	kg			*10,830	*10,830	*17,260	13,520	*12,450	9,000	9,450	6,600	7,250	5,090	*5,290	4,330	10.05 m
-1.5 m	kg	*10,180	*10,180	*14,960	*14,960	*17,590	13,190	12,840	8,710	9,240	6,410	7,140	4,990	*6,050	4,570	9.62 m
-3.0 m	kg	*14,870	*14,870	*20,400	*20,400	*16,920	13,180	*12,650	8,640	9,190	6,360			7,270	5,090	8.91 m
-4.5 m	kg	*20,320	*20,320	*21,120	*21,120	*15,150	13,420	*11,460	8,770	*8,700	6,500			*8,050	6,150	7.85 m
-6.0 m	kg			*15,750	*15,750	*11,680	*11,680	*8,490	*8,490					*7,890	*7,890	6.26 m

SK330		Boom: 6.5 m Arm: 2.6 m, Bucket: without Shoe: 600 mm (Heavy Lift)										
A \ B		3.0 m		4.5 m		6.0 m		7.5 m		At Max. Reach		Radius
7.5 m	kg									*8,750	8,570	7.06 m
6.0 m	kg					*9,350	*9,350	*8,600	7,690	*8,530	6,870	8.00 m
4.5 m	kg			*13,440	*13,440	*10,450	10,410	*9,010	7,440	8,330	6,000	8.58 m
3.0 m	kg					*11,750	9,760	*9,630	7,130	7,760	5,550	8.87 m
1.5 m	kg					*12,780	9,250	9,690	6,840	7,590	5,400	8.89 m
G.L.	kg			*17,790	13,460	13,090	8,960	9,500	6,660	7,790	5,520	8.66 m
-1.5 m	kg			*16,890	13,510	*12,910	8,900	9,460	6,630	8,480	5,990	8.15 m
-3.0 m	kg	*19,120	*19,120	*15,080	13,750	*11,700	9,040			*9,090	7,040	7.29 m
-4.5 m	kg	*14,520	*14,520	*11,710	*11,710					*8,570	*8,570	5.95 m

SK350LC		Boom: 6.5 m Arm: 3.3 m, Bucket: without Shoe: 600 mm (Heavy Lift)														
B \ A		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m		9.0 m		At Max. Reach		Radius
9.0 m	kg													*6,370	*6,370	6.56 m
7.5 m	kg									*7,800	*7,800			*5,840	*5,840	7.86 m
6.0 m	kg									*7,920	*7,920			*5,650	*5,650	8.71 m
4.5 m	kg							*9,710	*9,710	*8,480	7,770	*7,840	5,800	*5,650	5,530	9.25 m
3.0 m	kg					*15,070	*15,070	*11,140	10,240	*9,220	7,430	*8,140	5,650	*5,840	5,160	9.52 m
1.5 m	kg					*17,270	14,370	*12,400	9,660	*9,920	7,100	*8,470	5,480	*6,210	5,030	9.54 m
G.L.	kg					*18,030	13,890	*13,140	9,280	*10,380	6,870	8,350	5,370	*6,840	5,110	9.33 m
-1.5 m	kg			*15,400	*15,400	*17,660	13,790	*13,210	9,120	*10,400	6,760			*7,890	5,460	8.85 m
-3.0 m	kg	*17,520	*17,520	*22,230	*22,230	*16,350	13,920	*12,470	9,160	*9,670	6,810			*8,620	6,220	8.07 m
-4.5 m	kg			*18,150	*18,150	*13,770	*13,770	*10,460	9,410					*8,520	7,880	6.88 m

SK350LC		Boom: 6.5 m Arm: 4.15 m, Bucket: without Shoe: 600 mm (Heavy Lift)														
B \ A		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m		9.0 m		At Max. Reach		Radius
9.0 m	kg									*5,080	*5,080			*4,780	*4,780	7.56 m
7.5 m	kg													*4,470	*4,470	8.71 m
6.0 m	kg									*6,880	*6,880	*6,590	5,950	*4,360	*4,360	9.49 m
4.5 m	kg									*7,510	*7,510	*6,980	5,800	*4,380	*4,380	9.98 m
3.0 m	kg			*21,130	*21,130	*13,030	*13,030	*9,930	*9,930	*8,340	7,430	*7,410	5,590	*4,530	4,510	10.23 m
1.5 m	kg					*15,740	14,590	*11,400	9,680	*9,180	7,040	*7,870	5,370	*4,820	4,380	10.25 m
G.L.	kg			*10,830	*10,830	*17,260	13,760	*12,450	9,160	*9,830	6,720	8,180	5,190	*5,290	4,420	10.05 m
-1.5 m	kg	*10,180	*10,180	*14,960	*14,960	*17,590	13,420	*12,900	8,870	*10,130	6,530	8,070	5,090	*6,050	4,660	9.62 m
-3.0 m	kg	*14,870	*14,870	*20,400	*20,400	*16,920	13,410	*12,650	8,800	*9,890	6,480			*7,350	5,180	8.91 m
-4.5 m	kg	*20,320	*20,320	*21,120	*21,120	*15,150	13,650	*11,460	8,930	*8,700	6,620			*8,050	6,260	7.85 m
-6.0 m	kg			*15,750	*15,750	*11,680	*11,680	*8,490	*8,490					*7,890	*7,890	6.26 m

SK350LC		Boom: 6.5 m Arm: 2.6 m, Bucket: without Shoe: 600 mm (Heavy Lift)										
B \ A		3.0 m		4.5 m		6.0 m		7.5 m		At Max. Reach		Radius
7.5 m	kg									*8,750	8,700	7.06 m
6.0 m	kg					*9,350	*9,350	*8,600	7,810	*8,530	6,980	8.00 m
4.5 m	kg			*13,440	*13,440	*10,450	*10,450	*9,010	7,560	*8,500	6,100	8.58 m
3.0 m	kg					*11,750	9,920	*9,630	7,250	*8,580	5,650	8.87 m
1.5 m	kg					*12,780	9,400	*10,190	6,960	8,540	5,500	8.89 m
G.L.	kg			*17,790	13,690	*13,210	9,120	*10,440	6,780	8,780	5,620	8.66 m
-1.5 m	kg			*16,890	13,740	*12,910	9,060	*10,150	6,750	*9,070	6,090	8.15 m
-3.0 m	kg	*19,120	*19,120	*15,080	13,980	*11,700	9,200			*9,090	7,160	7.29 m
-4.5 m	kg	*14,520	*14,520	*11,710	*11,710					*8,570	*8,570	5.95 m

**Notes:**

- Do not attempt to lift or hold any load that is greater than these lift capacities at their specified lift point radius and heights. Weight of all accessories must be deducted from the above lift capacities.
- Lift capacities are based on machine standing on level, firm, and uniform ground. User must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, experience of personnel, etc.
- Arm top defined as lift point.
- The above lifting capacities are in compliance with ISO 10567. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Lifting capacities marked with an asterisk (\*) are limited by hydraulic capacity rather than tipping load.
- Operator should be fully acquainted with the Operator's and Maintenance Instructions before operating this machine. Rules for safe operation of equipment should be adhered to at all times.
- Lift capacities apply to only machine as originally manufactured and normally equipped by KOBELCO CONSTRUCTION MACHINERY CO., LTD.

## STANDARD EQUIPMENT

### ENGINE

- Engine, HINO J08EVV-KSDK, diesel engine with turbocharger and intercooler, Stage V certified
- Automatic engine deceleration
- Auto Idle Stop (AIS)
- Batteries (2 x 12V - 96Ah)
- Starting motor (24V - 5 kW), 60 amp alternator
- Automatic engine shut-down for low engine oil pressure
- Engine oil pan drain cock
- Double element air cleaner

### CONTROL

- Working mode selector (H-mode, S-mode and ECO-mode)
- Power Boost
- Heavy lift
- Object Handling Kit (boom and arm safety valve + hook)
- Extra N&B piping (proportional hand controlled)

### SWING SYSTEM & TRAVEL SYSTEM

- Swing rebound prevention system
- Straight propel system
- Two-speed travel with automatic shift down
- Sealed & lubricated track links
- Grease-type track adjusters
- Automatic swing brake

### HYDRAULIC

- Arm regeneration system
- Auto warm up system
- Aluminum hydraulic oil cooler
- Hydraulic fluid filter clog detector
- Hydraulic pressure adjustment function for N&B piping
- Quick hitch piping

### MIRRORS, LIGHTS & CAMERA

- Three rearview mirrors
- Three front working lights (two for boom, one for right strage box)
- Rear view camera

### CAB & CONTROL

- Two control levers, pilot-operated
- Horn, electric
- Cab light (interior)
- Luggage tray
- Large cup holder
- Detachable two-piece floor mat
- Headrest
- Handrails
- Intermittent windshield wiper with double-spray washer
- Skylight
- Tinted safety glass
- Pull-up type front window and removable lower front window
- Easy-to-read multi-display color monitor
- Automatic air conditioner
- Emergency escape hammer
- Suspension seat
- Radio, AM/FM stereo with speaker
- USB pin
- Top guard (ISO10262 : 1998)
- Geoscan
- Tow eyes
- Travel alarm
- Lower under cover

## OPTIONAL EQUIPMENT

- Various optional arms
- Wide range of shoes
- Additional track guide
- Two cab lights
- Rain visor (may interfere with bucket action)

- Cab guard
- Bigger capacity P4 pump and steel PTO housing
- Refueling pump
- Air suspension seat
- Right side camera

Note: This catalog may contain attachments and optional equipment that are not available in your area. And it may contain photographs of machines with specifications that differ from those of machines sold in your areas. Please consult your nearest KOBELCO distributor for those items you require. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice. Copyright by **KOBELCO CONSTRUCTION MACHINERY CO., LTD.** No part of this catalog may be reproduced in any manner without notice.

### **KOBELCO CONSTRUCTION MACHINERY CO., LTD.**

5-15, Kitashinagawa 5-chome, Shinagawa-ku, Tokyo 141-8626 JAPAN  
Tel: +81 (0) 3-5789-2146 Fax: +81 (0) 3-5789-2135  
[www.kobelco-kenki.co.jp/english\\_index.html](http://www.kobelco-kenki.co.jp/english_index.html)

Inquiries To: